

**Product and Option Schedule:**

		Tag		
Air Conditions		N9W9(Hum-1)	N10W10(Hum-1)	
External	Temperature			
	R.H.			
Entering	Temperature	-20.0°C	-20.0°C	
	R.H.	100%	100%	
Indoor	Temperature	26.0°C	26.0°C	
	R.H.	55%	55%	
Outdoor Air		Mechanical	Mechanical	
Mechanical	Total Air Flow	5999m³/hr	1750m³/hr	
	Outside Air			
Economizer	Total Air Flow			
	Mixed Air Temp.			
Natural	Building Volume			
	Air Changes/hr			
Humidifier Selection				
Calculated Load		75.15kg/hr	21.92kg/hr	
Humidifier Capacity		80.00kg/hr	30.00kg/hr	
Humidifier Model		SKE80M-400-3	SKE30M-400-3	
Signal		Modulating	Modulating	
Power		60kW	22kW	
Voltage/Phase/Cycle		400/3/50hz	400/3/50hz	
Amperage		87A	33A	
Dispersion Selection				
Dimensions Duct/AHU	Width	1280mm	670mm	
	Height	1000mm	570mm	
Air Temp. before humidification				
R.H.	Entering			
	Leaving			
Dispersion Model (# of tubes)		Multi Steam (8) H	Multi Steam (4) H	
Absorption distance		483mm	506mm	
Controls and Accessories				
Note				